

## RAJASTHAN MEDICAL SERVICES CORPORATION LTD.

D- Block, SwasthyaBhawan, TilakMarg, C-Scheme JAIPUR (Raj)



Ph. No. 0141-2223887, Fax No. 0141-2228065

CIN: U24232RJ2011SGC035067

E-Mail <u>-edepmrmsc-rj@nic.in</u>

No. F-8() RMSC/EPM/M-1/NIB-683/2022-23/

Dated: [6/11 22

## CLARIFICATION/CORRIGENDUM/ADDENDUM

Subject: Amendment in technical specification of bid document of item CCTV Camera Surveillance System, under No. F-8() RMSC/EPM/M-1/NIB-683/2022-23/249 date: 30.06.2022

In reference to subject cited above NIB-683, various representation received from the firms and issues raised by the bidder are examined by the competent authorities and technical committee. The following clarification/corrigendum/addendum is issued for inclusion in bid document of items as below:-

## Revised Technical Specifications of CCTV Camera Surveillance System:-

- 1. Image Sensor: 2.0 megapixel or above progressive scan CMOS or better
- 2. Frame Rate: 1920x1080 (1 fps-25/30 fps) or better
- 3. Resolution:  $1920 (H) \times 1080 (V)$  or better
- 4. Weather proof (For outside and Indoor installation)
- 5. IP camera for day and night use.
- 6. IR Range of 30Mtr or better.
- 7. Minimum Illumination: 0.01Lux or better
- 8. Weatherproof Standard: IP67
- 9. White Balance: Auto
- 10. Lens: 3.6mm lens or better
- 11. Day/Night support
- 12. Operating Temperature: -10°C to 55°C or better
- 13. PoE(802.3af)
- 14. Video Compression: H.264 or better compression
- 15. Plastic I/O box (outdoor type) for fixing camera on it.
- 16. Shutter Speed: Auto/ Mannual, 1/3~1/100000s
- 17. Angle of view: 3.6 or better
- 18. Smart Phone Supported.
- 19. Channel Network Video Recorder (NVR):
  - 1. Video Compression: H.265 or better compression
  - 2. IP video input: 1-ch Up to 4K resolution(Supports H.265 + /H.265/ H.264 + / H.264 IP cameras) or better
  - 3. HDMI/VGA output: HDMI output: 4k or better
  - 4. VGA output: 1080p or better
  - 5. Video bit rate: 32 Kbps to 6 Mbps
  - 6. Network protocols :IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS, NTP; Multicast; ONVIF (Profile S)
  - Capacity: Up to 6 TB capacity for each disk (2TB hard disk to be provided with system)
  - 8. Network interface: 1, RJ45 10/100Mbps self-adaptive Ethernet interface
  - 9. USB interface: 2 × USB 2.0 or better 1 Panel.
  - 10. Working temperature: -10 °C to +55 °C (+14 °F to +131 °F) or better
  - 11. NVR solution must be compatible to monitor surveillance via remote viewing using internet connection.





- 12. Remote/Mouse to be provided with NVR system for operating.
- 13. I/O rack with fan, shelf and PDU to be provided with NVR system.
- 14. Audio in/ Output: 1-ch RCA IN and 1-ch RCA Out
- 15. Recording Resolution: 5MP/ 4MP/ 3MP/ 1080p/ UXGA/ 720p/ VGA/ 4CIF/ DCIF/ 2CIF/ CIF/ QCIF
- 20. a. Port PoE switch
  - 1. Port Number: 16x 10/100Mbps PoE+ ports + 2x10/100/1000 MBPS Upliak.
  - Standard: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at
  - 3. Packet forwarding rate: 5.36 Mbps or better
  - 4. PoE standard: Port 1 to 16, IEEE 802.3af/ IEEE 802.3at, full duplex Ethernet data link layers
  - 5. Long Range: port 1 to 16 transmission distance 250m or better

## **General Condition:**

- 1. Camera and NVR must be in compliance with CE, FCC and UL/BIS certifications.
- 2. Camera and NVR should be of same make for better integration
- 3. CCTV product to be manufactured by a make whose quality system is in compliance with the ISO-9001:2015 and Environmental Management Certificate ISO14001:2004.
- 4. Demonstration to be given as and when required. Schedule for the same will be informed in advance.
- 5. 30 meter connecting CAT 6 cable to operate camera (for power and NVR connection) to be provided with each camera, free of cost.
- 6. Installation will be provided free of cost.
- 7. 2TB hard disk to be provided with each NVR.
- 8. CMS and Mobile Software for surveillance to be provided free of cost.
- 9. Full HD (1080p) surveillance grade monitor 32" or more with HDMI and VGA port with wall mount stand.
- 10. Guarantee Period of 3 years.
- 11. The camera bidder must submit declaration regarding OEM own manufacturing on OEM letter head.
- 12. Comprehensive Maintenance Service: CMC will be given @ 3 % of net rate excluding GST (as applicable) and yearly escalation of 5 % on last year's CMC price. The CMC may be awarded for five years (on yearly basis) after Guarantee period of 3 years.

Note:- All above mentioned specification are generic in nature, will promote healthy competition & will not encourage Pro- Single Bid participation.

Note:- Please note that all above amendments/corrigendum in technical specifications/bid conditions is the integral part of (Section-VIII) and the bid document. This corrigendum/ addendum should be signed and annexed with bid document. All other terms & conditions remains the same.

Executive Director (EPM)

RMSCL, Jaipur